

# 747 FRESH SCENT MASTIC REMOVER

## V.O.C. COMPLIANT

Sentinel 747 Fresh Scent Mastic Remover is the original, most widely used and specified remover designed to clean and remove black asphalt and solvent based mastics and clear thin spread adhesives commonly found under 9" and 12" vinyl floor tile.

### Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

#### USE CONDITIONS

This product works best at room temperature (70°F). Colder temperatures can affect product performance.

#### PREPARATION

Protect walls, cabinetry, trim, drains, cracks and adjoining flooring with plastic and/or absorbent dikes (oil absorbing powder, kitty litter, rags) to keep mastic remover and liquified adhesive contained as well as to protect from overspray or agitated material in subsequent steps.

#### STEP 1:

Wet the entire adhesive surface with product. This may be done by using a garden sprayer or by applying 747 directly to the floor and using a mop or floor squeegee to move it over the surface of the adhesive. DO NOT overapply. Allow 747 to soak and penetrate for 10-20 minutes.

#### STEP 2:

Scrape the bulk of the softened adhesive from the surface with a floor scraper. This will help increase the coverage of 747 and reduce the amount of liquid generated and make final clean up easier. Place in a container for disposal.

#### STEP 3:

Reapply 747 as in Step One. To fully lift and liquify adhesive residue from the floor agitate with a short-bristled broom, hand held or rotating floor scrubber with stripper pads. Squeegee resulting mixture into puddles and solidify with an absorbent. Remove absorbed material to a container and dispose. Follow all local, state and federal regulations when disposing of waste.

#### STEP 4:

Wash and rinse the floor thoroughly using Sentinel 317 Multi-Purpose Cleaner and Degreaser and water or a soap and water solution. Allow subfloor to dry for at least 24 hours and test moisture levels before reflooring.

#### WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

### SPECIFICATIONS

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Clear
<b>Color:</b>	None
<b>Odor:</b>	Low
<b>pH:</b>	Not applicable
<b>Flash Point:</b>	>199.4°F
<b>Boiling Point:</b>	363 - 381°F
<b>Self-Ignition Temp:</b>	421°F
<b>Vapor Pressure:</b>	<0.2 mm Hg@68°F
<b>V.O.C. Content:</b>	<15 g/L (calc.)*
<b>Shelf Life:</b>	60 Months
<b>Coverage Rate:</b>	100 -200 sq. ft./gal

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



**800-373-0633 or [www.senpro.com](http://www.senpro.com)**

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445